

MONO 72 SOLAR LINE

SCM-350

30 YEARS
LINEAR POWER WARRANTY


15 YEARS
PRODUCT WARRANTY

POSITIVE POWER OUTPUT TOLERANCE

HAILSTORM RESISTANCE

ULTRA-LIGHT ALUMINUM FRAME

ANTI-REFLECTIVE GLASS



MONOCRYSTALLINE SOLAR MODULE

You don't have enough room for your system, yet you don't want to compromise energy efficiency? SOLAR CALL is the right fit for you!

- High efficiency: with the dimensions of a 72cell solar module, these panels can reach an extremely high power output thanks to the use of high-efficiency cells.
- Captivating design: this monocrystalline solar panel has been designed to be elegant and sober, perfect for each kind of solar system.
- Maximum stability and strenght: we employ top-quality materials for our products, thus ensuring their long-lasting reliability and their stability in any environmental conditions.

72 CELLS

72

MONO
CRYSTALLINE

M

5 BUS BAR

5

156 x 156mm
6 x 6"



SILVER
FRAME



WHITE
BACKSHEET



PERC TECHNOLOGY

Passivated Emitter and Rear Cell

SOLAR CALL believes in technological innovation aimed at the continuous improvement of its products. Therefore we deploy PERC technology cells for our monocrystalline modules, which allow to achieve higher efficiency.

ELECTRICAL CHARACTERISTICS (STC)*

Nominal Output (Pmax)	350 W
Flash Test Power Tolerance	0/+5
Voltage at Pmax (Vmp)	38 V
Current at Pmax (Imp)	9.22 A
Open Circuit Voltage (Voc)	46.2 V
Short Circuit Current (Isc)	9.94 A
Maximum System Voltage	1500 V
Maximum Series Fuse Rating	15 A
Module Efficiency	18.03%

*STC (Standard Test Condition): Irradiance 1000 W/m²; Module Temp. 25 °C; Air Mass 1.5

SCM-350

MECHANICAL CHARACTERISTICS

Solar Cells	72 (6 x 12) monocrystalline	Diodes	3 Bypass diodes serviceable
Solar Cells Size	156 x 156 mm / 6 x 6"	Junction Box	IP67 rated
Front Cover	3.2 mm / 0.12" thick, low iron tempered glass	Connector	MC4 or compatible connector
Back Cover	TPT (Tedlar-PET-Tedlar)	Cables Length	900 mm / 35.4"
Encapsulant	EVA (Ethylene vinyl acetate)	Cables Section	4.0 mm ² / 0.006 in ²
Frame	Anodized aluminium alloy, double wall	Dimensions	1957 x 992 x 40 mm / 77 x 39 x 1.57"
Frame finishing	Silver	Weight	22.5 kg / 49.6 lbs
Backsheet finishing	White	Max. Load	Certified to 5400 Pa

TEMPERATURE CHARACTERISTICS

Temperature Coefficient of Pmax	-0.40 % / °C	Operating Temperature	-40 °C ~ +85 °C
Temperature Coefficient of Voc	-0.32 % / °C	NOCT**	45±2 °C
Temperature Coefficient of Isc	0.04 % / °C	**Nominal Operation Cell Temperature: Irrad. 800 W/m ² ; Air 20 °C; Wind speed 1 m/s	



PACKAGING

Palettenabmessungen	2000 x 1200 x 1200 mm / 79 x 47 x 47"	Weight	622 kg / 1371 lbs
Anzahl Module pro Palette	27	Pallets Stacked	up to two

CERTIFICATIONS

Fire resistance rating	1 (UNI 9177)
------------------------	--------------

CURRENT/VOLTAGE CHARACTERISTICS



DIMENSIONS

